



Compressor Oil RP

PRODUCT DESCRIPTION

Top quality base oils with rust and oxidation inhibitor used for lubrication of Reciprocating air compressors.

APPLICATION

Reciprocating compressor with single and multi stages having discharge temperature upto 215 °C. Stationary portable & Semi portable units. Specific equipment manufacturer's recommendations should be followed.

Not recommended for use in breathing air compressors.

BENEFITS

- Protect against rust, wear & oxidation
- Reduced downtime
- Trouble-free operations
- Prolonged Oil service life
- Prolonged Compressors life

TYPICAL PROPERTIES

TEST	TYPICAL		RESULT	
ISO Viscosity Grade	32	46	68	100
Flash Point 0C	214	216	228	246
Pour Point 0C	-12	-12	-12	-12
Viscosity:				
@ 40 °C, cSt	30.6	44	65	95.5
@ 100 °C, cSt	5.3	6.7	8.5	10.8
Viscosity Index	104	103	100	97
Acid Number, mg KOH/g	0.10	0.10	0.10	0.10
Product Code	PAN 901003	PAN 901004	PAN 901005	PAN 901006

The Panther Trade Mark is owned by Panther Lubricants Limited, London, England

Health & Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

Note: Due to continual product research and development, the information contained herein is subject to change without notification.
Typical Properties may vary slightly