



# PANTHER EP GREASE

## PRODUCT DESCRIPTION

Top quality grease manufactured from high viscosity index mineral based oil, lithium thickener, EP additives and Rust and Oxidation inhibitors for use in automotive and industrial applications.

## APPLICATION

**Panther EP Greases** are ideal for General plant lubrication, Automotive, Construction, Earthmoving, Quarrying, Mining, Agricultural Equipment, Wheel Bearing, Industrial rolling elements bearings.

Usable Temperature in Continuous Service is 120 °C

Maximum Temperature for Short term exposure is 175 °C (NLGI 1, 2 and 3)

## BENEFITS

- Ease of Application
- Reduces Lubrication Costs
- Reduces Maintenance
- Protects against Rust & Corrosion

## TYPICAL PROPERTIES

NLGI	TYPICAL		RESULT
	1	2	3
Dropping point@ 50 °C, mins	195	195	205
Oil Viscosity:			
@ 40 °C, cSt	170	170	208
@ 100 °C, cSt	15.2	15.2	17.2
Penetration, Worked@25	325	280	235
Thickener (Lithium)	5	7.5	10
Timken OK Load, KG	19	19	19
Product Code	PAN 101003	PAN 101004	PAN 101005

**The Panther Trade Mark is owned by Panther Lubricants Limited, London, England**

### **Health & Safety**

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

**Note:** Due to continual product research and development, the information contained herein is subject to change without notification.  
Typical Properties may vary slightly