



PANTHER UD GREASE

PRODUCT DESCRIPTION

Top quality grease manufactured from high viscosity index mineral based oil, Lithium thickener, and special EP additive, rust and oxidation inhibitors and tackiness agent for use in automotive and industrial applications for ball and roller bearings at high temperature, where water or salt water contamination is a concern.

APPLICATION

Panther UD Greases are ideal for Dredging Equipment, Mining, Quarrying ,Offshore Oil drilling; Off-highway construction; Logging and forestry; Marine deck equipment, General industrial greasing; Pulp and paper machinery; Agricultural tractors.

Usable Temperature in Continuous Service is -20 to 140 °C

BENEFITS

- Wide temperature range application
- Reduces Lubrication Costs
- Reduces Maintenance
- Protects against Rust & Corrosion

TYPICAL PROPERTIES

TEST	TYPICAL	RESULTS
NLGI	1	2
Dropping point@ 50 °C, mins	174	180
Oil Viscosity:		
@ 40 °C, cSt	350	470
@ 100 °C, cSt	21	25
Penetration, Worked@ 25 °C	325	280
Thickener (Lithium), m %	5	9
Timken OK Load, kg	32	32
Product Code	PAN 101008	101009

The Panther Trade Mark is owned by Panther Lubricants Limited, London, England

Health & Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

Note: Due to continual product research and development, the information contained herein is subject to change without notification.
Typical Properties may vary slightly